



LAUNDRY SOLUTIONS
YOU CAN *DEPEND* ON.


MAYTAG® COMMERCIAL ENERGY ADVANTAGE™ ON-PREMISES DRYING TUMBLER

MORE ENERGY-SAVING SOLUTIONS THAN ANY OTHER BRAND

Maytag built the first appliance ever to receive the ENERGY STAR® label. Today we offer more high-efficiency laundry appliances than any other brand — from energy-efficient dryers to highly efficient ENERGY STAR®-qualified washers — to help you save money and build profits.

MICROPROCESSOR CONTROLS

Advanced computer controls let you program drying cycles with desired drying times, temperatures and cool-down. Then select the cycle with the simple touch of a button.



FOR YOUR OPERATION:

- Auto Cycle Helps Prevent Laundry Overheating
- Fast-Drying Axial Airflow System
- Extra-Large Door Opening
- Digital Display Shows Time Remaining In Cycle
- Extra-Large Lint Compartment
- Factory-Installed Risers


BUILT-TO-LAST™ FEATURES:

- S.A.F.E. System Puts Out Dryer Fires
- Heavy-Duty Motor

MDG31PN



MAYTAG'S
MOST EFFICIENT
MULTI-LOAD DRYER.



Dimensions will vary according to adjustment of leveling legs; add 1/2" (1.3 cm) minimum.

Maytag® Energy Advantage™ On-Premises Drying Tumbler MICROPROCESSOR CONTROL

		Energy Advantage™ Multi-Load Dryer
DRYER SPECIFICATIONS		
MODEL	MDG31PN	
CAPACITY		
Lbs. (kg)	30 (13.6)	
Cu. ft. (cu. m)	11.04 (.312)	
TUMBLER		
Diameter — in. (cm)	30 (76.2)	
Depth — in. (cm)	27 (68.5)	
MOTOR		
HP (kw) Drive Motor	1/4 (.186)	
AIRFLOW		
Cfm (cmm)	360 (10.2)	
HEAT INPUT		
BTU/hr. (kcal/hr.)	55,000 (13,860)	
GAS INLET		
In. M.N.P.T.	3/8	
VOLTAGE/BREAKER/FUSE REQUIREMENTS		
Voltage	120	
Amps	10.3	
COLOR		
White	•	
APPROXIMATE WEIGHT		
Crated — lbs. (kg)	446 (202.3)	
Uncrated — lbs. (kg)	425 (192.8)	
DIMENSIONS		
A) Height not including legs — in. (cm)	44 ²⁵ / ₃₂ (113.7)	
B) Width — in. (cm)	31 ¹ / ₈ (79.1)	
C) Depth not including door handle — in. (cm)	34 ⁵ / ₈ (87.6)	
D) Exhaust diameter — in. (cm)	6 (15.2)*	
E) Riser Height — in. (cm)	22 (55.88)	
Door opening — in. (cm)	19 ³ / ₈ (49.2)	
* Requires 8" (20.3 cm) material if venting horizontally; 10" (25.4 cm) if venting vertically.		
See specific instructions for proper installation.		
Because of continuous product improvement, Maytag reserves the right to change specifications without notice.		



NEW YORK CITY
M.E.A.



MAYTAG® LIMITED WARRANTY

2 YEARS — ALL PARTS
5 YEARS — SHELL, WELDED FRAME ASSEMBLY, BASKET, SHAFT ASSEMBLY, BEARINGS AND SEALS

For a period from the date of original purchase through the times listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.

